

Rec 3-12-87
Dms 1799

DOUGLAS AIRCRAFT COMPANY
ATTN MYA ANDERSON
3855 LAKEWOOD BLVD
LONG BEACH, CA 90846

DOW CORNING CORPORATION
MATERIAL SAFETY DATA SHEET

MATL NAME: DOW CORNING(R) 90-006 SEALANT
EMERGENCY TELEPHONE NO. (517) 496-5900

SECTION I - GENERAL INFORMATION

MANUFACTURERS NAME: DOW CORNING CORPORATION
ADDRESS: SOUTH SAGINAW ROAD, MIDLAND MI 48686

PROPER SHIPPING NAME(49CFR 172.101): NONE
D.O.T. HAZARD NAME(49CFR 172.101): NONE
D.O.T. ID NO(49CFR 172.101): NONE
D.O.T. HAZARD CLASS(49CFR 172.101): NONE
RCRA HAZARD CLASS(40CFR 261)(IF DISCARDED): NONE
E.P.A. PRIORITY POLLUTANTS(40CFR 122.53): IRON
NFPA = NATIONAL FIRE PROTECTION ASSOCIATION - 704
HEALTH (NFPA): 1 FLAMMABILITY (NFPA): 1 REACTIVITY (NFPA): 0
CAS NO: MIXTURE DOW CORNING WARNING CODE: 76
GENERIC DESCRIPTION: SILICONE

SECTION II - HAZARDOUS INGREDIENT

DOW CORNING(R) 90-006 SEALANT % 100 TLV (UNITS): NOT ESTABLISHED

ONLY THOSE INGREDIENTS LISTED IN THIS SECTION HAVE BEEN DETERMINED TO BE HAZARDOUS AS DEFINED IN 29 CFR 1910.1200. AN INGREDIENT MARKED WITH AN ASTERISK(*) IS ALSO LISTED IN 29 CFR 1910.1200(D) #4 AS KNOWN OR SUSPECTED CARCINOGEN.

COMMENT: NONE

DOW CORNING CORPORATION
MATERIAL SAFETY DATA SHEET

MATL NAME: DOW CORNING(R) 90-006 SEALANT

SECTION III - EFFECTS OF OVEREXPOSURE

EYES: MAY IRRITATE WITH SLIGHT PAIN, REDNESS, AND POSSIBLE MINOR CORNEAL INJURY.

SKIN: SINGLE, PROLONGED EXPOSURE (HOURS) CAUSES NO KNOWN EFFECT. SEVERAL REPEATED, PROLONGED EXPOSURES MAY CAUSE SLIGHT IRRITATION.

INHALATION: NO IRRITATION TO NOSE OR THROAT EXPECTED. NO INJURY IS LIKELY FROM RELATIVELY SHORT EXPOSURE.

ORAL: AMOUNTS TRANSFERRED TO THE MOUTH BY FINGERS, ETC., DURING NORMAL OPERATIONS SHOULD NOT CAUSE INJURY.

COMMENT: NO KNOWN ADVERSE CHRONIC HEALTH EFFECTS, BUT UNNECESSARY EXPOSURE TO ANY CHEMICAL SHOULD BE AVOIDED. THIS PRODUCT, AS WITH ANY CHEMICAL, MAY ENHANCE ALLERGIC CONDITIONS ON CERTAIN PEOPLE. WE DO NOT KNOW OF ANY MEDICAL CONDITIONS THAT MIGHT BE AGGRAVATED BY EXPOSURE TO THIS PRODUCT.

SECTION IV - EMERGENCY AND FIRST AID PROCEDURES

EYES: FLUSH WITH WATER FOR 15 MINUTES.

SKIN: WIPE OFF AND FLUSH WITH WATER.

INHALATION: NO PROBLEM.

ORAL: NO PROBLEM.

COMMENT: NONE

SECTION V - FIRE AND EXPLOSION DATA

FLASH POINT (METHOD USED): OPEN CUP ABOVE 250°F/121°C

AUTOIGNITION: NOT DETERMINED

FLAMMABILITY LIMITS IN AIR : LOWER:NA UPPER: NA

EXTINGUISHING MEDIA: WATER WATER FOG X CO2 X DRY CHEMICAL X FOAM X OTHER

SPECIAL FIRE FIGHTING PROCEDURES: SELF CONTAINED BREATHING APPARATUS AND PROTECTIVE CLOTHING SHOULD BE WORN IN FIGHTING FIRES INVOLVING CHEMICALS

UNUSUAL FIRE AND EXPLOSION HAZARDS: NONE KNOWN TO DOW CORNING

COMMENTS: NA - NOT APPLICABLE

SECTION VI - PHYSICAL DATA

BOILING POINT(@ 760 MM HG): ABOVE 300°F/149°C.

SPECIFIC GRAVITY (AT 77 DEG F/25 DEG C): 1.35

MELTING POINT: NOT APPLICABLE

VAPOR PRESSURE (AT 77 DEG F/25 DEG C): LESS THAN 5 MM.

VAPOR DENSITY (AIR = 1 AT 77 DEG F/25 DEG C): NOT APPLICABLE

PERCENT VOLATILE BY VOLUME (%): LESS THAN 5%

EVAPORATION RATE (ETHER = 1): LESS THAN 1

SOLUBILITY IN WATER(%): LESS THAN 0.1%

ODOR, APPEARANCE, COLOR: VERY LITTLE ODOR, PASTE LIKE, RED

NOTE: THE ABOVE INFORMATION IS NOT INTENDED FOR USE IN PREPARING PRODUCT SPECIFICATIONS. CONTACT DOW CORNING BEFORE WRITING SPECIFICATIONS

DOW CORNING CORPORATION
MATERIAL SAFETY DATA SHEET

MATL NAME: DOW CORNING(R) 90-006 SEALANT

SECTION VII - REACTIVITY DATA

STABILITY: STABLE

INCOMPATABILITY(MATERIAL TO AVOID): OXIDIZING MATERIAL CAN CAUSE A REACTION.

CONDITIONS TO AVOID: NOT APPLICABLE

HAZARDOUS DECOMPOSITION PRODUCTS: METAL OXIDES, SILICON DIOXIDE, CARBON DIOXIDE
AND TRACES OF INCOMPLETELY BURNED CARBON PRODUCTS.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

CONDITIONS TO AVOID: NOT APPLICABLE

COMMENTS: NONE

SECTION VIII - SPILL, LEAK AND DISPOSAL PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: REMOVE PRODUCT
AND USE ABSORBENT MATERIAL TO TAKE CARE OF ANY OIL-LIKE RESIDUES.

PROTECTIVE EQUIPMENT:

EYES: USE PROPER PROTECTION -- SAFETY GLASSES AS A MINIMUM.

SKIN: WASHING AT MEALTIME AND END OF SHIFT IS ADEQUATE.

INHALATION: NO RESPIRATORY PROTECTION REQUIRED.

WASTE DISPOSAL METHOD: DOW CORNING SUGGESTS THAT ALL LOCAL, STATE AND FEDERAL
REGULATIONS CONCERNING HEALTH AND POLLUTION BE REVIEWED TO DETERMINE APPROVED
DISPOSAL PROCEDURES. CONTACT DOW CORNING IF THERE ARE ANY DISPOSAL QUESTIONS.

D.O.T. (49CFR 171.8)/E.P.A. (40CFR 117) SPILL REPORTING INFORMATION
HAZARDOUS SUBSTANCE: NONE REPORTABLE QUANTITY: NOT APPLICABLE
CONCENTRATION OF HAZARDOUS SUBSTANCE: NOT APPLICABLE
REPORTABLE QUANTITY OF PRODUCT: NOT APPLICABLE

COMMENTS: NONE

SECTION IX - ROUTINE HANDLING PRECAUTIONS

PROTECTIVE EQUIPMENT:

EYES: USE PROPER PROTECTION -- SAFETY GLASSES, AS A MINIMUM.

SKIN *: WASHING AT MEALTIME AND END OF SHIFT IS ADEQUATE.

INHALATION: NO RESPIRATORY PROTECTION REQUIRED.

VENTILATION:

LOCAL EXHAUST: NONE SHOULD BE NEEDED
MECHANICAL (GENERAL): RECOMMENDED

SUITABLE RESPIRATOR: NONE SHOULD BE NEEDED

THESE PRECAUTIONS ARE FOR ROOM TEMPERATURE HANDLING, USE AT ELEVATED TEMPERATURE
MAY REQUIRE ADDED PRECAUTIONS.

* GOOD PRACTICE REQUIRES THAT GROSS AMOUNT OF ANY CHEMICAL BE REMOVED
FROM THE SKIN AS SOON AS PRACTICAL, ESPECIALLY BEFORE EATING OR SMOKING.

COMMENTS: NONE

SECTION X - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: STORE BELOW 90°F/32°C.
USE REASONABLE CARE.

OTHER PRECAUTIONS: NONE KNOWN TO DOW CORNING.

COMMENTS: TRACES OF FORMALDEHYDE AND OTHER THERMAL DECOMPOSITION PRODUCTS
MAY FORM AT TEMPERATURES ABOVE 150°C IN THE PRESENCE OF AIR. PROVIDE ADEQUATE
VENTILATION WHEN HANDLING AT ELEVATED TEMPERATURES.

DOW CORNING CORPORATION
MATERIAL SAFETY DATA SHEET

MATL NAME: DOW CORNING(R) 90-006 SEALANT

THESE DATA ARE OFFERED IN GOOD FAITH AS TYPICAL VALUES AND NOT AS A PRODUCT SPECIFICATION. NO WARRANTY, EITHER EXPRESSED OR IMPLIED, IS HEREBY MADE. THE RECOMMENDED INDUSTRIAL HYGIENE AND SAFE HANDLING PROCEDURES ARE BELIEVED TO BE GENERALLY APPLICABLE. HOWEVER, EACH USER SHOULD REVIEW THESE RECOMMENDATIONS IN THE SPECIFIC CONTEXT OF THE INTENDED USE AND DETERMINE WHETHER THEY ARE APPROPRIATE.

PREPARED BY: JACK L. SHENEBERGER

LAST REVISION DATE: OCTOBER 29, 1985

PREVIOUS REVISION DATE: MAY 27, 1981

DATE: MARCH 03, 1987

(R) INDICATES REGISTERED OR TRADEMARK OF THE DOW CORNING CORPORATION.